

L4™ Light



Protecting you for life's **best** moments.

TECHNICAL DATA SHEET

GVS-RPB.COM

The L4 Light is designed to attach ergonomically to the Nova 3® blast helmet to provide bright focused light in dark/low light environments without adding unnecessary height and weight to the users helmet.

The battery is mounted to the users belt to remove any unnecessary weight off the head.

Packages	Part #
L4 Light - USA	09-502
L4 Light - Global	09-502-G

Compatible with the following respirator

Nova 3

Application ranges (including but not limited to the following)

Any industrial application performed wearing a Nova 3 respirator in low light/low vision environments e.g. abrasive blasting.

Specifications

Power supply

- Powered by 3.7V Lithium polymer battery
- Charging power: Universal 110-240 volt adapter.
- Power cords available include US, EU, UK and AU/NZ.
- Charging time: Approximately 4 hours to fully charge.

Battery run time

- Up to 4 hours
- 350 charge cycles

Brightness

- 650 lumens

Transportation

Assemblies with batteries ship following UN3481 requirements.

Materials	Parts
Nylon/ABS	Housing
TPU	Strap
Polycarbonate	Lenses
PVC coating	Cables
Lithium-polymer	Battery

Weight

Added weight to head-top	0.32lbs / 145g
Including battery	0.86lbs / 390g



RPB L4 Light

Operating temperature

14°F to 140°F / -10°C to 60°C

Storage temperature

14°F to 113°F / -10°C to 45°C <90%RH

Recommended storage temperature is 40°F to 70°F (4°C to 21°C) in order to maximize the life of the battery.

Warranty

1 year. Conditions apply, visit gvs-rpb.com/legal for full details.

Accessories & consumables

Description	Part #
Outer lens	09-522
Easily replaceable due to abrasive bounce back.	
Additional battery pack	09-532-2



Employers

Read the L4 Light and the Nova 3 respirator instruction manuals and carry out the employer responsibilities.

Provide the manuals to all users.

Product users

Read the L4 Light and the Nova 3 respirator instruction manuals and follow the product user safety instructions.

Manuals are regularly updated.

Current version of manual and for other languages:

gvs-rpb.com/resources

Contact

RPB Safety - Global Headquarters

2807 Samoset Rd, Royal Oak, MI 48073, USA

T: 1-866-494-4599

E-mail: sales@gvs.com

gvs-rpb.com