

# Sena Tufftalk M



GVS-RPB.COM

## Approvals & Standards

Compliant with ANSI S3.19 when used with T-Link and Z-Link

**ISO9001**  
CERTIFIED COMPANY

## Features

The Sena Tufftalk M is a mesh and bluetooth communication headset.

**Ease of Use:** With Mesh Intercom™, the communication setup is as simple as a click of a button. Once you enter Open Mesh, you'll be able to speak with a virtually limitless number of users

**Hands-Free Communication:** The Tufftalk M features full-duplex communication, allowing you to speak with your team without needing a "push-to-talk" button.

## Compatible with

All configurations of the RPB T-Link® and RPB Z-Link®

## Part number

Sena Tufftalk M Mounted Headset Kit	18-534
-------------------------------------	--------

## Level of protection

### Noise Reduction Rating

Headset alone	NRR (ANSI S3.19-1974, US) -24 dB SNR (EN 352-1:2020, EU) -28 dB
Headset mounted to T-Link®	NRR (ANSI S3.19-1974, US) -31 dB
Headset mounted to Z-Link®	NRR (ANSI S3.19-1974, US) -31 dB

## Audio Communication

### Bluetooth

Bluetooth 4.1  
Headset Profile (HSP)  
Hands-Free Profile (HFP)  
Advanced Audio Distribution Profile (A2DP)  
Audio Video Remote Control Profile (AVRCP)

### Noise Cancellation:

Advanced Noise Control™

### Codec:

Built-in SBC Codec

### FM Radio:

Radio frequency specifications: 76 ~ 108MHz  
10 preset station memory

### Mesh Network

Mesh 2.0 Intercom™ Technology

### Intercom

Working Distance	Bluetooth Intercom™: up to 400 meters (440 yards) in open space
	Mesh Intercom™: up to 1.1 km (0.7 miles) in open space* *can extend up to 4.4 km (2.8 miles) between a minimum of 6 users (in open space).
Supports up to	Bluetooth Intercom™: 4 users
	Mesh Intercom™ (Open Mesh): virtually limitless users
	Mesh Intercom™ (Group Mesh): 24 users



## Specifications

### Dimensions

Height	192 mm (7.6 in)
Depth	97 mm (3.8 in)
Width	150 mm (5.9 in)

### Weight

Mount Earmuff Type	368 g (13.0 oz)
--------------------	-----------------

### Temperature

Operating	-10°C to +55°C
Storage	+15°C to +30°C
Charging	0°C to +45°C

### Battery

Talk Time	Bluetooth intercom™: up to 13 hours Mesh intercom™: up to 8 hours
Charging Time	3 hours
Quick Charge	20 minutes of charging equals 3 hours Intercom™
Type	Lithium Polymer Battery
Capacity	1,400 mAh



### Employers

Read the Sena Tufftalk M Users Guide and carry out the employer responsibilities. Provide the manuals to all users.

### Product users

Read the Sena Tufftalk M Users Guide and follow the product user safety instructions. Manuals are regularly updated.

For current version of manual & other languages visit:  
[senaindustrial.com](http://senaindustrial.com)

GVS-RPB® Safety Ltd.  
2807 Samoset Rd, Royal Oak, MI 48073, USA  
T: 1-866-494-4599  
E-mail: [sales@gvs.com](mailto:sales@gvs.com)  
[gvs-rpb.com](http://gvs-rpb.com)