



H: 178 mm D: 130 mm W: 166 mm



H: 108 mm D: 52 mm W: 68 mm

**Weight**

Mask + Filters: 550 g  
Filters: 200 g

**Shelf Life**

5 years (mask & filters) See storage conditions on Instructions for Use. Filters are re-usable and changeable.

**Standards**

Facemask EN 136:1998 Class 1  
EN166:2001 Class 1 & K (anti-scratch)  
Cartridge filter EN 14387:2004+A1:2008 A2P3 R D

**Efficiency**

P3 >99,95% for 0,3 µ particulate  
At 5000 ppm:  
> 35 minutes Cyclohexane (C<sub>6</sub>H<sub>12</sub>)



**Patent Pending**

1. Particulate pleated filter (total length 645 mm)
2. Activated carbon treated for gas adsorption
3. Designed to help airflow diffusion and full usage of the activated carbon
4. Inhalation valve



**Material**

- Inner mask body in Medical Grade TPE
- Visor in polycarbonate overmolded with silicone frame
- Headband in silicone
- Covers in PE
- Valve body in nylon with silicone diaphragms
- Gas Filters: Activated carbon sealed into a ABS Shell
- Particulate filters: Mechanical type multi-layer HESPA Synthetic media with TPE flexible overmolded / encapsulated. Particulate filters are integrated with the carbon element

Part #	Description
FFM221L	Elipse® Full Face A2P3 Respirator Package also includes: ■ Replaceable filters
FIL253L	Elipse® A2P3 Replacement Cartridges Pair
SPM1001	Elipse® Full Face Carry Case
SPM1002	Elipse® Full Face Face Face Fit Test
SPM1003	1 pc Tearoff Kit

**Applications**

**Welding and Grinding:** Metal Fumes and Dust in confined spaces (gas welding)

**Constructions:** Paint, Moulds

**Manufacturing:** Solvents , various Organic Gases

**Automotive & Marine:** Coal Dust, Silica Dust

**Agriculture:** Pesticides